DESCRIPTION

DATA MATCHING METHOD, DATA MATCHING APPARATUS AND DATA MATCHING PROGRAM

Technical Field

The present invention relates to a data matching method and a data matching system (apparatus) which is applied to an object whose state changes and matches a data of a state change object at a certain time with a data at a different time of the object. Also, the present invention relates to a data matching program which is applied to an object whose state changes and matches a data of a state change object at a certain time with a data at a different time of the object. In particular, the present invention relates to a data matching method and a data matching system (apparatus) which match from an image and voice of biometrics information such as a face, a voiceprint or the like of a person at a certain time, an image and voice at a different time of the biometrics information, and relates to a data matching program which matches from an image and voice of biometrics information such as a face, a voiceprint or the like of a person at a certain time, an image and voice at a different time of the biometrics information.

Background Art

When matching is executed for a data of an object whose state changes, there may be a trouble at a matching of a data of certain time with a data at a different time. For example, in the case of the data with regard to the object whose state changes as represented by biometrics information, such as the face, voice and the like of a person, ageing causes the loss of the feature of the youth, and the feature after the ageing appears, or the change in emotion causes the feature of the face and voice to be unnoticeable, or the other feature to be outstanding. Thus, the data in the state at a certain time is different from the data in the state at the other time even in the data of the same object, and may possibly result in the trouble at the matching.

As an example of the method of generating the data after the shape is changed by adding a feature from the data at a certain time, a method of generating the face image after the ageing from the face in the younger age when the aging is added to the face image. For example, a computer graphics (CG) is used to draw the feature after the ageing, such as wrinkle and the like, to the face in the younger age and consequently generate the face image after the ageing from the face in the younger age.

Also, in U.S. Patent No.6556196, an image processing method is described, which in a case of processing a face image, refines the addition of an aging feature and an expression feature to an tmage by using a three-dimensional model, and can add even the unclear feature to the image. By this image processing method, a typical model of a deformable face is generated from a three-dimensional face data stored in a face database and an input face image is pasted on a generated model. Then, in order to give a feature change including the state change, a modeler is used to deform the model.

In Japanese Laid Open Patent Application (JP-P 2000-132675A), a face identifying and matching method is described, which is characterized by studying in advance the feature of an image variation caused by a difference in photographing conditions or photographing timing for each classified class, and selecting a class from a difference between two face images where at least one of the photographing condition and the photographing timing is different, and determining the feature amount where the feature amount of the image variation in the class selected from the two face images is reduced, respectively, and then executing the face identification and matching in accordance with the feature amounts of the two face images.

In Japanese Laid Open Patent Application
(JP-P 2003-233671A), a method of estimating a
development of at least one state in a body outer
surface portion of a target person is described, by
5   which a first data indicating at least one state is
received, a second data to reflect how at least one
state on the body outer surface is expected to be
developed in association with a time elapse is
received, and an estimation development of at least
10 one state in accordance with the first data and the
second data is generated and then the estimation
development to the target person is sent.

Disclosure of Invention
15   In the case of matching the data by adding a
feature to generate a state changed data, the
procedure for generating the feature change caused
by the aging, the expression change or the like is
not always established. When the generating
20 procedure for the feature change is not established,
a human must imitate an actually existing feature and
write on the data. Thus, a manual process or a
semi-automatic process which requires an effort close
to the manual work must be executed.
25   Also, in the case that the data is matched by
using the state change data generated by adding a
feature, differently from the drawing of the local

relatively clear feature, the addition of the state
change that is global and difficult to grasp
intuitively by drawing on is difficult. Thus, the
state change that is global and difficult to grasp
5   intuitively is difficult to treat.

In the image processing method noted in U.S.
Patent No.6556196, a pre-prepared sample is used and
the state feature is given to the image. Thus, even
in the case of generating the face image of arbitral
10   person, the feature of the same state change is
generated on the same portion. For example, in the
case of generating the face image of arbitral person,
the same wrinkle is generated on the same portion.

Also, in the image processing method noted in
15   U.S. Patent No.6556196, the usage where the state
feature suitable for the matching face is added is
not assumed. Thus, whether or not the generated
sample has the state feature suitable for the face
matching is uncertain. Hence, there is a possibility
20   that a face image to which an unnatural state feature
is added is generated.

Also, the image processing method described
in U.S. Patent No.6556196 does not assume the purpose
where the state change is added to the image by
25   determining the change given to the image which is
corresponding to the state. Thus, when the state
change to be added to the image is determined, the

work load on a user is heavy.

It is therefore a subject of the present invention to provide a data matching method, a data matching apparatus and a data matching program which, for generating a state changed data, use for matching the state changed data where the peculiarity of an object is considered in accordance with the relative relation of the same object, and can consequently improve the matching performance of the data involving the state change.

Also, the present invention has the subject to provide a data matching method, a data matching apparatus and a data matching program which add a statistical state change to the data before the state change, and use for the matching of the state change data to which the feature of the global state change is added, and can consequently improve the matching performance of the data involving the state change.

Also, the present invention has the subject to provide a data matching method, a data matching apparatus and a data matching program which give a correspondence of a configuration component between respective categories and use for the matching of the state change data to which a typical state change for each age is added, and can consequently improve the matching performance of the data at a particular state.

Moreover, the present invention has the subject to provide a data matching method, a data matching apparatus and a data matching program which can add the statistical state change to the data prior to the state change and automatically generate the state change data to be generated at the time of the matching and can suppress the load on a worker at the time of the data matching.

A data matching method according to the present invention includes: a configuration component accumulation step accumulating a configuration component generated by decomposing a measuring quantity of an object by a predetermined method and a plurality of states of the object each of which is corresponding to the configuration component; a component decomposition step decomposing a measuring quantity of a matching target object into the configuration component at a predetermined state of the plurality of states; a parameter conversion step converting a parameter corresponding to the configuration component of the predetermined state into a converted parameter of a second state of the plurality of states different from the predetermined state; a state change data generating step generating a state change data by adding a predetermined state change to a data of the matching target object by using the configuration

component accumulated in the configuration component

accumulation step and the converted parameter; and

a matching step matching the state change data and

a matching data accumulated in advance. Under such

5   configuration, the data generated by adding the state

information to an input data is used for executing

the matching. As a result, the matching performance

of the data involving the state change is improved.

       In the data matching method according to the

10   present invention, the predetermined method is the

principal component analysis.

       A data matching method according to the

present invention includes: a configuration

component accumulation step accumulating a

15   configuration component generated by decomposing a

measuring quantity of an object by a predetermined

method and a plurality of states of the object each

of which is corresponding to the configuration

component; a connecting step connecting a parameter

20   corresponding to the configuration component at a

first state of the plurality of states and a parameter

corresponding to the configuration component at a

second state through a conversion using a learning;

a state change data generation step generating a state

25   change data of the second state by converting a data

of the matching target object at the first state

through a conversion using the learning; and a

matching step matching the state change data and a matching data accumulated in advance. According to such configuration, the matching performance of the data involving the state change is improved.

5 Moreover, the configuration of the data matching apparatus is simplified. The "learning" implies the generation of a face image, for example, in accordance with the conversion using a neural network, by defining state-specific data of a same person as a

10 learning data.

In the data matching method according to the present invention, the data of the matching target is a biometrics data of human being. The biometrics data means, for example, an image of a portion of a

15 human body exemplified as the face and the fingerprint, the one-dimensional data of the voice such as sound and the like, and the three-dimensional data of the face shape.

In the data matching method according to the

20 present invention, each of the plurality of states corresponds to a state at a different time through a course of aging.

In the data matching method according to the present invention, the measuring quantity is an image

25 of a face.

The data matching apparatus according to the present invention is a computer having a function of

executing each of the steps included in the data

matching method according to the present invention.

The data matching program according to the present

invention instructs the computer to execute the data

5   matching method according to the present invention.

The data matching method according to the

present invention is the data matching method for

matching the data of the object of the matching target

with the data included in a data group and

10   corresponding to the object of the matching target

and is characterized by including: a matching data

accumulating step of accumulating in advance the data

group registered for the matching; a component

decomposing step of decomposing the data of the

15   matching target into the configuration component in

a predetermined state; a parameter converting step

of converting the parameter corresponding to the

configuration component in the predetermined state

into a parameter (attained by coefficients c_i, d_i of

20   the configuration component) in a state different

from the predetermined state; a state change data

generating step of accumulating the configuration

component of the data classified into each state, and

using the accumulated configuration component and the

25   parameter converted at the parameter converting step,

and then generating the state change data where a

predetermined state change is given to the data of

the matching target; and a matching step of matching the state change data generated at the state change data generating step with a matching data group accumulated at the matching data accumulating step.

Also, the data matching method is the data matching method, which matches the data of the object of the matching target with the data included in the data group and corresponding to the object of the matching target and may include: a matching data accumulating step of accumulating in advance the data group registered for the matching; a state change data generating step of generating the state change data where the data in the predetermined state is changed into the data in the different state from the predetermined state, in accordance with the conversion formed through the learning through the data classified into each state; and a matching step of matching the state change data generated at the state change data generating step with the matching data group accumulated at the matching data accumulating step.

Also, the data matching method is the data matching method, which matches the biometrics data of a person with the biometrics data included in the data group and corresponding to a person and may include: the matching data accumulating step of accumulating in advance the data group registered for

the matching; a component decomposing step of decomposing the biometrics data of the matching target into the configuration component in the predetermined state; the parameter converting step

5   of converting the parameter corresponding to the configuration component in the predetermined state into the parameter in the state different from the predetermined state; the state change data generating step of accumulating the configuration component of

10   the biometrics data classified into each state, and using the accumulated configuration component and the parameter converted at the parameter converting step, and then generating the state change data where the predetermined state change is given to the biometrics

15   data of the matching target; and the matching step of matching the state change data generated at the state change data generating step with the matching data group accumulated at the matching data accumulating step.

20   Also, the data matching method is the data matching method, which matches the biometrics data of the person with the biometrics data included in the data group and corresponding to a person and may include: the matching data accumulating step of

25   accumulating in advance the data group registered for the matching; the state change data generating step of generating the state change data where the

biometrics data in the predetermined state is changed

into the biometrics data in the state different from

the predetermined state, in accordance with the

conversion formed through the learning through the

5   biometrics data classified into each state; and the

matching step of matching the state change data

generated at the state change data generating step

with the matching data group accumulated at the

matching data accumulating step.

10   Also, in the data matching method, the

component decomposing step decomposes the biometrics

data into the configuration component after the

predetermined ageing, and the parameter converting

step converts the parameter corresponding to the

15   configuration component after the predetermined

ageing into the parameter after the ageing different

from the predetermined ageing, and the state change

data generating step accumulates the configuration

component of the biometrics data classified into each

20   ageing, and uses the accumulated configuration

component and the parameter converted at the

parameter converting step, and then generates the

aging data (attained by the state change data) where

the predetermined aging is given to the biometrics

25   data, and the matching step matches the aging data

generated at the state change generating step with

the matching data group accumulated at the matching

data accumulating step.

Also, in the data matching method, the state change data generating step generates the aging data where the biometrics data after the predetermined ageing is changed into the biometrics data after the ageing different from the predetermined ageing, in accordance with the conversion formed through the learning through the biometrics data classified into each ageing, and the matching step matches the aging data generated at the state change generating step with the matching data group accumulated in the matching data accumulating step.

Also, the data matching method is the data matching method of matching a face image of a person of a matching target with a face image included in a face image group and corresponding to a person and may include: a matching data accumulating step of accumulating in advance the face image group registered for the matching; a component decomposing step of decomposing the face image into the configuration component in a predetermined expression; a parameter converting step of converting a parameter corresponding to the configuration component in the predetermined expression into a parameter in the expression different from the predetermined expression; an expression change data generating step of accumulating the configuration

component of the face image classified into each expression, and using the accumulated configuration component and the parameter converted at the parameter converting step and then generating an

5   expression change data (attained by the state change data) where a predetermined expression change is

。   given to the face image; and the matching step of matching the expression change data generated at the expression change data generating step with the

10   matching data group accumulated at the configuration component accumulating step.

Also, the data matching method is the data matching method of matching the face image of a person of the matching target with the face image

15   corresponding to the person included in the face image group and may include the matching data accumulating step of accumulating in advance the face image group registered for the matching; the expression change data generating step of generating the expression

20   change data where the face image in the predetermined expression is changed into the face image in the expression different from the predetermined expression, in accordance with the conversion using the study through the face image classified into each

25   expression; and the matching step of matching the expression change data generated at the expression change data generating step with the matching data

group accumulated at the matching data accumulating step.

The data matching apparatus according to the present invention is the data matching apparatus which matches the data of the object of the matching target with the data corresponding to the object of the matching target included in the data group and is characterized by including: a component decomposing unit (attained by a component analyzing unit 101) for decomposing the data of the matching target into the configuration component in the predetermined state; a parameter converting unit (attained by a component coefficient converting unit 103) for converting the parameter corresponding to the configuration component in the predetermined state into the parameter in the different state from the predetermined state; a state change data generating unit (attained by a state change data generating unit 102) for accumulating the configuration component of the data classified into each state, and using the accumulated configuration component and the parameter converted by the parameter converting unit and then generating the state change data where a predetermined state change is given to the data of the matching target; a matching data accumulating unit (attained by a matching data accumulating unit 104) for accumulating in advance

the data group registered for the matching; and a matching unit (attained by a matching unit 105) for matching the state change data generated by the state change data generating unit with the matching data group accumulated by the matching data accumulating unit.

Also, the data matching apparatus is the data matching apparatus, which matches the data of the object of the matching target with the data included in a data group and corresponding to the object of the matching target and may include: a state change data generating unit (attained by a state change data generating unit 102b) for generating the state change data where the data in the predetermined state is changed into the data in the state different from the predetermined state, in accordance with the conversion using the study through the data classified into each state; the matching data accumulating unit for accumulating in advance the data group registered for the matching; and the matching unit for matching the state change data generated by the state change data generating unit with the matching data group accumulated by the matching data accumulating unit. According to such configuration, it is possible to improve the matching performance of the data involving the state change and also possible to simplify the configuration of

the data matching apparatus.

Also, the data matching apparatus is the data matching apparatus, which matches the biometrics data of the person with the biometrics data corresponding to the person included in the data group and may include: the component decomposing unit for decomposing the biometrics data of the matching target into the configuration component in the predetermined state; the parameter converting unit for converting the parameter corresponding to the configuration component in the predetermined state into the parameter in the state different from the predetermined state; the state change data generating unit for accumulating the configuration component of the biometrics data classified into each state, and using the accumulated configuration component and the parameter converted by the parameter converting unit, and then generating the state change data where the predetermined state change is given to the biometrics data of the matching target; the matching data accumulating unit for accumulating in advance the data group registered for the matching; and the matching unit for matching the state change data generated by the state change data generating unit with the matching data group accumulated by the matching data accumulating unit.

Also, the data matching apparatus is the data

matching apparatus, which matches the biometrics data of a person with the biometrics data included in the data group and corresponding to a person and may include: the state change data generating unit for generating the state change data where the biometrics data in the predetermined state is changed into the biometrics data in the different state from the predetermined state, in accordance with the conversion using the study through the biometrics data classified into each state; the matching data accumulating unit for accumulating in advance the data group registered for the matching; and the matching unit for matching the state change data generated by the state change data generating unit with the matching data group accumulated by the matching data accumulating unit.

Also, the component decomposing unit decomposes the biometrics data into the configuration component after the predetermined ageing, the parameter converting unit converts the parameter corresponding to the configuration component after the predetermined ageing into the parameter after the ageing different from the predetermined ageing, the state change data generating unit accumulates the configuration component of the biometrics data classified into each ageing, and uses the accumulated configuration component and the parameter converted

by the parameter converting unit, and then generates
the aging data where the predetermined aging is given
to the biometrics data, and the matching unit matches
the aging data generated by the state change

5   generating unit with the matching data group
accumulated by the matching data accumulating unit.

      Also, the state change data generating unit
may generate the aging data where the biometrics data
after the predetermined ageing is changed into the

10   biometrics data after the ageing different from the
predetermined ageing, in accordance with the
conversion formed through the learning through the
biometrics data classified into each ageing, and the
matching unit may match the aging data generated by

15   the state change generating unit with the matching
data group accumulated by the matching data
accumulating unit.

      Also, the data matching apparatus is the data
matching apparatus for matching the face image of a

20   person of the matching target with the face image
included in the face image group and corresponding
to a person and may include: a component decomposing
unit for decomposing the face image into the
configuration component in the predetermined

25   expression; a parameter converting unit for
converting the parameter corresponding to the
configuration component in the predetermined

expression into the parameter in the expression different from the predetermined expression; an expression change data generating unit (attained by the state change data generating unit 102) for

5   accumulating the configuration component of the face image classified into each expression, and using the accumulated configuration component and the parameter converted by the parameter converting unit and then generating the expression change data where

10   the predetermined expression change is given to the face image; the matching data accumulating unit for accumulating in advance the face image group registered for the matching; and the matching unit for matching the expression change data generated by

15   the expression change data generating unit with the matching data group accumulated by the configuration component accumulating unit.

Also, the data matching apparatus is the data matching apparatus, which matches the face image of

20   a person of the matching target with the face image included in the face image group and corresponding to the person and may include: an expression change data generating unit (attained by the state change data generating unit 102b) for generating the

25   expression change data where the face image in the predetermined expression is changed into the face image in the expression different from the

predetermined expression, in accordance with the
conversion using the study through the face image
classified into each expression; the matching data
accumulating unit for accumulating in advance the
5   face image group registered for the matching; and the
matching unit for matching the expression change data
generated by the expression change data generating
unit with the matching data group accumulated by the
matching data accumulating unit.

10   The data matching program according to the
present invention is the data matching program which
matches the data of the object of the matching target
with the data included in a data group and
corresponding to the object of the matching target
15   and is characterized by instructing a computer having
the matching data accumulating unit for accumulating
in advance the data group registered for the matching
to execute: a process for decomposing the data of the
matching target into the configuration component in
20   the predetermined state; a process for converting the
parameter corresponding to the configuration
component in the predetermined state into the
parameter in the state different from the
predetermined state; a process for accumulating the
25   configuration component of the data classified into
each state, and using the accumulated configuration
component and the converted parameter and then

generating the state change data where the predetermined state change is given to the data of the matching target; and a process for matching the generated state change data with the matching data group accumulated by the matching data accumulating unit.

Also, the data matching program is the data matching program which matches the data of the object of the matching target with the data included in a data group and corresponding to the object of the matching target and instructs the computer having the matching data accumulating unit for accumulating in advance the data group registered for the matching to execute: a process for generating the state change data where the data in the predetermined state into the data in the state different from the predetermined state, in accordance with the conversion formed through the learning by using the data classified into each state; and the process for matching the generated state change data with the matching data group accumulated by the matching data accumulating unit. According to such configuration, it is possible to improve the matching performance of the data involving the state change and also possible to simplify the configuration of the data matching apparatus.

According to the present invention, the state

change data is generated to then execute the matching. Thus, for the state change object, only the data of the object at the certain time can be used to execute the matching of the high precision. Thus, when the state change data is generated, in accordance with the relative relation of the same object, the state change data where the peculiarity of the object is considered is used for the matching. Hence, it is possible to improve the matching performance of the data involving the state change.

According to the present invention, even if there is only the biometrics data such as the image, the voice and the like at a certain time, by generating the data at the time of the state change and then matching with the registration information, it is possible to improve the performance of the matching of the person identification, the crime investigation, the academic investigation or the like in a security system.

Brief Description of Drawings

Fig. 1 is a block diagram showing an example of the configuration of a data matching apparatus according to the present invention;

Fig. 2 is a flowchart showing an example of the data matching process where the data matching apparatus matches a face image;

Fig. 3 is a block diagram showing another example of the configuration of the data matching apparatus;

Fig. 4 is a flowchart showing another example of the data matching process where the data matching apparatus matches the face image;

Fig. 5 is a block diagram showing an example of the configuration of the component analyzing apparatus;

Fig. 6 is a block diagram showing an example of the configuration of the state change generating apparatus;

Fig. 7 is a block diagram showing an example of the configuration of the component coefficient converting apparatus; and

Fig. 8 is a block diagram showing an example of the configuration of the state change data generating apparatus.

Best Mode for Carrying Out the Invention
THE FIRST EMBODIMENT.

The first embodiment of the present invention will be described below with reference to the drawings. Fig. 1 is a block diagram showing an example of the configuration of the data matching apparatus according to the present invention. Here, the case where the shape is changed through the aging, a face

image is used as a state change data, and the data matching apparatus is used for matching a face image at a certain time with a face image at a different time is explained.

5   The state change is not limited to the aging. Then, the data matching apparatus may be the apparatus for matching the data involving the different state change such as the expression change of a face and the like. Also, the state change data is not limited 10 to the face image, and may be the data such as the image of the various portions of the human body, a fingerprint and the like, the one-dimensional data such as the voice, sound and the like, and the three-dimensional biometrics data of a face shape and 15 the like. Also, the state change data may be the data of an animal other than the human and a plant and the data with regard to the object that is aged while having the individual property similarly to a living thing.

20   As shown in Fig. 1, the data matching apparatus includes: a component analyzing unit 101 for analyzing the component of an input data 11; a state change data generating unit 102 for generating a state (ageing) change data of the input data 11; 25 a component coefficient converting unit 103 for correlating between the databases of respective states (ageing); a matching data accumulating unit

104 for accumulating in advance the matching data;
and a matching unit 105 for matching the state
(ageing) change data with the data accumulated by the
matching data accumulating unit 104.

5   Also, the state change data generating unit
102 has a plurality of state-specific (ageing-
specific) databases DB1, ..., DBi, ..., DBn, which
accumulate the configuration components of the data
classified into respective states (ageing). Each of
10   the databases accumulates the configuration
component obtained by decomposing the measuring
quantity of an object by using a predetermined method
such as the principal component analysis and the like.
Hereafter, for comprehensively representing the
15   state-specific databases DB1 to DBn, or for
representing any of the state-specific databases, we
refer merely as the state-specific database.

          In this embodiment, the matching data
accumulating unit 104 is realized by, for example,
20   a magnetic disc device. The component analyzing unit
101, the component coefficient converting unit 103
and the matching unit 105 are realized by, for example,
a central processor in a computer and a program
executed by the central processor. The state change
25   data generating unit 102 is realized by, for example,
the magnetic disc device, the central processor in
the computer and the program executed by the central

processor.

The component analyzing unit 101 has a
function for re-configuring the face image so that
the deviation is the smallest, by using the
configuration component in the state-specific
database Bi corresponding to state (ageing)
information 12 of the face image which is the input
data 11. In this embodiment, the component analyzing
unit 101 selects the state-specific database Bi
corresponding to the state of the face image of the
input data 11, for example, in accordance with the
state information 12 inputted by the state change data
generating unit 102, and re-configures the face
image.

For example, when the component analysis is
executed, a linear component analysis such as the
principal component analysis and the like is used in
many cases. When the face image is configured in the
linear coupling of principal components, the face
image is represented by the equation (1).

Equation (1):

$Ip = c1P1 + c2P2 + ... + cmPm$

(Pi: Principal component, ci: Coefficient)

In this embodiment, as the component
analyzing unit 101, a minimum deviation coefficient
set ci where the deviation from an input face image
I0 is the smallest is selected from the face images

represented by the equation (1). The component
analyzing unit 101 sends the selected minimum
deviation coefficient selection set c_i through the
state-specific databases DB_i of the state change data
generating unit 102 to the component coefficient
converting unit 103.

The state change data generating unit 102 has
the plurality of state-specific databases DB_1, ...,
DB_i, ..., DB_n that accumulate the configuration
components of the data classified into the respective
states (ageing). Also, the state change data
generating unit 102 has a function for passing a
coefficient set c_i corresponding to each state-
specific database calculated by the component
analyzing unit 101 to the component coefficient
converting unit 103.

Also, the state change data generating unit
102 has a function for re-configuring the face image
by using: a coefficient set d_i converted by the
component coefficient converting unit 103 for the
state-specific database which is different from the
state-specific databases selected by the component
analyzing unit 101; and the configuration component
inside the different state-specific database. Also,
the state change data generating unit 102 has a
function for sending a re-configuration face image
J_p as a state (ageing) change data to the matching

unit 105. The re-configuration face image Jp is represented by using an equation (2) as the linear coupling of the coefficient set di in a principal component Qi inside the state-specific database, when
5   the principal component analysis is used.

Equation (2):

$Jp=d1Q1+d2Q2+ \ldots +dmQm$

       The state-specific database Bi accumulates the components, which are generated by converting
10   into major elements {U1, U2, ..., Uj, ..., Up} among the elements constituting each image, from face images {A1, A2, ..., Ai, ..., Ap} in a certain age, through a predetermined calculation, as the configuration components. For example, in the case
15   of using the principal component analysis, the state-specific database accumulates the value, which is obtained by singular value decomposition of the matrix where a pixel Ai (x, y) of each image is arranged as a column vector, as the configuration component.
20   In this case, the matrix where the pixel Ai (x, y) of each image is arranged as the column vector is represented by an equation (3).

[Numeral 1]

$$A = \begin{bmatrix} A_1(0,0) & \cdots & A_i(0,0) & \cdots & A_p(0,0) \\ \vdots & \cdots & \vdots & \cdots & \vdots \\ A_1(x,y) & \cdots & A_i(x,y) & \cdots & A_p(x,y) \\ \vdots & \cdots & \vdots & \cdots & \vdots \\ A_1(m,n) & \cdots & A_i(m,n) & \cdots & A_p(m,n) \end{bmatrix} \quad \text{EQUATION (3)}$$

The state-specific database accumulates, as the configuration components, the former p column vectors {U1, U2, ..., Uj, ..., Up} of an orthogonal

5   matrix obtained by applying the singular value decomposition represented by the equation (4) to the matrix represented by the equation (3)

Equation (4):

$A = USV^t$

10   By the way, in the equation (4), S is the matrix where the elements except diagonal components are 0, and the diagonal components are arranged in a descending order of an absolute value.

Also, in order to correlate the respective

15   state-specific databases, between the two state-specific databases, the face images of the same persons are generated in advance correspondingly to

the number of the components to be used, respectively.
For example, when 30 configuration components are
used, in the two state-specific databases, the face
images in both of the states (ageing) are generated

5   correspondingly for 30 or more persons, and the
configuration components of the respective state-
specific databases are generated and accumulated in
advance.

The component coefficient converting unit

10 103 has a function for converting a coefficient that
is multiplied to the configuration component of the
state-specific database. For example, the case of
using the principal component analysis is
exemplified.

15   For example, the two state-specific
databases DBi, DBj are used, and the principal
components of the databases DBi, DBj are assumed to
be Pi (i=1, ..., n) and Qj (j=1, ..., n), respectively,
and the coefficients of the principal components are

20 assumed to be ci (i=1, ..., n) and dj (j=1, ..., n),
respectively. In this case, in order to convert from
the coefficient ci to the coefficient dj, a plurality
of face images Ip, Jp belonging to both of the states
(ageing) respectively corresponding to the databases

25 DBi, DBj under the faces of the same persons are used.
Here, the face images Ip, Jp are represented by
equations (5) and (6) respectively, by using the

equation (1).

Equation (5):

$Ip = c1P1 + c2P2 + \ldots + cnPn$

Equation (6):

5 $Jp = d1Q1 + d2Q2 + \ldots + dnQn$

Thus, supposing that the conversion from the coefficients c_i to the coefficients d_j is a linear conversion T, and supposing a coefficient set of a person A is represented by {CiA, DjA}, a coefficient

10 set of a person B is represented by {CiB, DjB} and so on. Then, the coefficient set of the person B {CiB, DjB} etc. is represented by an equation (7).

Equation (7):

[DjA, DjB, ...] = T[CiA, CiB, ...]

15 Here, in the equation (7), CiA and DjA are the column vectors where the coefficients c_i, d_i in the equation (4) and the equation (5) are vertically arranged. Thus, the linear conversion T can be calculated by using an equation (8), when C=[CiA,

20 CiB, ...] and D=[DjA, DjB, ...] are assumed.

Equation (8):

$T = DC^t(CC^t)^{-1}$

The component coefficient converting unit 103 may execute the conversion from c_i to d_j by using

25 a nonlinear conversion. For example, the component coefficient converting unit 103 may define the coefficient set {c_i, d_j}, in which they correspond

to the databases DBi, DBj in the faces of the same persons, respectively, as the learning data, and execute the coefficient conversion by using the neural network.

5   The matching data accumulating unit 104 is a database for accumulating the data for the matching and accumulates in advance the data registered for the matching. The matching data accumulating unit 104 is realized by, for example, a data storage unit

10 of the usual matching apparatus. The matching data accumulating unit 104 accumulates in advance the data groups for a current face image of a person and a face image having no expression, for example, as the data for the matching.

15   The matching unit 105 having a function for comparing and matching the state change data generated by the state change data generating unit 102 with the registration data accumulated by the matching data accumulating unit 104 and outputting

20 a matching result 18. For example, the matching unit 105 determines the difference between the state (ageing) change data and the registration data and judges the data, in which the determined difference is the smallest, as the data of the person itself.

25 The method is not limited to those using the difference. The matching unit 105 can execute the matching by using the other matching method.

Also, the matching unit 105 matches the plurality of state change data generated by the state change data generating unit 102 with the registration data, as shown in Fig. 1. Thus, the matching unit 105

5 matches the plurality of state change data with the registration data, and then regards the data, which has the minimum difference among the entire differences, as the data of the person itself, and can consequently execute the matching corresponding

10 to the state (ageing) change. When the state (ageing) of the data accumulated by the matching database (the matching data accumulating unit 104) is known, the matching unit 105 may match the state change data of only the state (age) corresponding to the

15 registration data with the registration data. If so, a matching time can be reduced.

The operations will be described below. Fig. 2 is the flowchart showing an example of the data matching process where the data matching apparatus

20 matches the face image. The component analyzing unit 101 inputs the input data 11 of a matching target, in accordance with an input operation by a user (Step S101). In this example, the component analyzing unit 101 inputs the face image of the matching target as

25 the input data 11.

Also, the state change data generating unit 102 inputs the state information 12 indicating the

state of the input data 11, in accordance with the input operation of the user (Step S102). For example, the state change data generating unit 102 inputs the year and year zone (age) of the person of the face image in the input data 11. Also, for example, the state change data generating unit 102 inputs the information indicating the expression of the face image in the input data 11, such as the feeling and the like, as the state information 12.

The component analyzing unit 101 selects the state-specific database Bi corresponding to the state of the input data 11 of the matching target, in accordance with the state information 12, from the state-specific databases DB of the state change data generating unit 102 (Step S103). Also, the component analyzing unit 101 extracts the configuration component from the selected state-specific database, analyzes the input data 11 and calculates a configuration component coefficient (Step S104). Also, the component analyzing unit 101 sends the calculated configuration component coefficient through the state-specific database in the state change data generating unit 102 to the component coefficient converting unit 103.

The component coefficient converting unit 103 converts the configuration component coefficient calculated by the component analyzing unit 101, into

the configuration component coefficient corresponding to the state-specific database other than the state-specific database selected by the component analyzing unit 101 (Step S105). The state change data generating unit 102 extracts the configuration component from the state-specific database corresponding to the configuration component coefficient after the conversion and generates the state change data in accordance with the configuration component coefficient converted by the component coefficient converting unit 103 and the extracted configuration component (Step S106).

The matching unit 105 extracts the registration data from the matching data accumulating unit 104. Then, the matching unit 105 matches the state change data generated by the state change data generating unit 102 with the registration data accumulated by the matching data accumulating unit 104, and outputs the matching result 18 (Step S108).

As mentioned above, according to this embodiment, since the data before the state change and after the state change is generated to execute the matching, for the state change object, only the data of the object at a certain time can be used to then execute the matching of the high precision. Thus, at the time of the generation of the state change data, by using for the matching the state change data where

the peculiarity of the object is considered on the basis of the relative relations of the same object, it is possible to improve the matching performance of the data involving the state change.

5   Also, in this embodiment, the feature of the object is decomposed into the configuration components. Thus, by using even the statistical state feature that is difficult to manually represent, it is possible to execute the matching of the high

10   precision. Hence, by using for the matching the state change data where the statistical state change is added to the data before the state change and the feature of the rough state change is also added, it is possible to improve the matching performance of

15   the data involving the state change.

          Also, according to this embodiment, it can be processed independently of the time axis. Thus, when the process for giving the aging as the state change is executed, the matching of the high precision can

20   be performed on another aging of not only the ageing change but also the aging towards the young direction and the like.

          Also, according to this embodiment, since the state change data in the plurality of states can be

25   generated and used for the matching, by coping with the plurality of state changes, it is possible to execute the matching of the high precision. Also,

according to this embodiment, by giving the correspondence of the configuration component between the respective state categories and using for the matching the state change data in which the typical state change in each age is added to the data before the state change, it is possible to improve the matching performance of the data in the particular state.

Also, according to this embodiment, since the addition of the state change to be generated at the time of the matching can be automatically executed, the burden on the worker at the time of the matching can be reduced. Thus, it is possible to add the statistical state change to the data before the state change, and automatically generate the state change data to be generated at the time of the matching and consequently reduce the burden on the worker at the time of the data matching.

Moreover, according to this embodiment, the existing many matching systems can be used to realize the data matching apparatus. Thus, it is possible to easily assemble the system (data matching apparatus) and possible to change the system.

THE SECOND EMBODIMENT.

The second embodiment of the present invention will be described below with reference to the drawings. Fig. 3 is a block diagram showing

another example of the configuration of the data

matching apparatus. This embodiment differs from

the first embodiment in that the data matching

apparatus does not include the component analyzing

5   unit 101 and the component coefficient converting

unit 103, in the configuration elements shown in Fig.

1. Also, in this embodiment, the process of the state

change data generating unit 102b in the data matching

apparatus differs from the process of the state change

10   data generating unit 102 shown in the first

embodiment.

In this embodiment, the state change data

generating unit 102b inputs a face image, which is

the input data 11, to the state-specific database

15   corresponding to the state (ageing) information 12

of the input data 11. The state change data

generating unit 102b directly sends the input data

11 to the other state-specific databases except the

state-specific database corresponding to the input

20   data 11 and generates the face images (state change

data) of the states (ageing) other than the state of

the input data 11. Then, the state change data

generating unit 102b sends the generated face image

to the matching unit 105.

25   In this embodiment, the state change data

generating unit 102b generates the state change data

by directly converting the face image from a certain

state into the other state without using the configuration component. For this reason, between the respective state-specific databases, the data classified into each state (ageing) of the same person is accumulated in advance to generate a neural network. Then, the state change data generating unit 102b uses the pre-generated neural network and generates the converted face image. In this embodiment, for example, the state change data generating unit 102b defines the pre-accumulated state-specific database of the same person as the learning data, and uses the neural network and then executes the converting process and consequently generates the face image.

In this embodiment, the large quantity of the state-specific data of the same person is required, because of the learning in the neural network, as compared with the first embodiment. However, the configuration of the data matching apparatus can be simplified.

The operations will be described below. Fig. 4 is a flowchart showing another example of the data matching process where the data matching apparatus executes the matching of face images. The state change data generating unit 102b inputs the input data 11 of the matching target, in accordance with the input operation by the user (Step S201). In this embodiment, the state change data generating unit

102b inputs the face image of the matching target as the input data 11.

Also, the state change data generating unit 102b inputs the state information 12 indicating the state of the input data 11, in accordance with the input operation of the user (Step S202). For example, the state change data generating unit 102b inputs the year and year zone (age) of the person of the face image of the input data 11. Also, for example, the state change data generating unit 102b inputs the information indicating the expression of the face image of the input data 11, such as the feeling and the like, as the state information 12.

The state change data generating unit 102b converts the input data 11 into the state change data of the state (age) other than the state of the input data 11 (Step S203). In this case, the state change data generating unit 102b generates the state change data by using the already-learned neural network, in accordance with the state information 12.

The matching unit 105 extracts the registration data from the matching data accumulating unit 104. Then, the matching unit 105 matches the state change data generated by the state change data generating unit 102b with the registration data accumulated by the matching data accumulating unit 104, and outputs the matching result 18 (Step S204).

As mentioned above, according to this embodiment, the data matching apparatus, even if the component analyzing unit 101 and component coefficient converting unit 103 shown in the first embodiment do not exist, can obtain the effect similar to the data matching apparatus indicated in the first embodiment. Thus, it is possible to improve the matching performance of the data involving the state change and also possible to simplify the configuration of the data matching apparatus.

THE THIRD EMBODIMENT.

The third embodiment of the present invention will be described below with reference to the drawings. This embodiment corresponds to the apparatus where the data matching apparatus in the first embodiment is made into the specific apparatus. In this embodiment, the data matching apparatus includes: a component coefficient converter where the component coefficient converting unit 103 is made into an apparatus; the state change generator where the state change data generating unit 102 is made into an apparatus; the component analyzer where the component analyzing unit 101 is made into an apparatus; the matching data accumulator where the matching data accumulating unit 104 is made into an apparatus; and the matching device where the matching unit 105 is made into an apparatus.

Fig. 5 is a block diagram showing an example of the configuration of the component analyzer 101a where the component analyzing unit 101 is made into an apparatus. As shown in Fig. 5, the component analyzer 101a includes a calculator 101b, an input data storage device 101c and a configuration component storage device 101d.

The input data storage device 101c is specifically realized by a memory and a magnetic disc device. The input data storage device 101c has a function for accumulating the face image of the input data 11. The configuration component storage device 101d is specifically realized by a memory and a magnetic disc device. The configuration component storage device 101d has a function for accumulating the configuration component sent from the state change generator 102a where the state change data generating unit 102 is made into an apparatus.

The calculator 101b is realized by a CPU that is operated in accordance with a program. The calculator 101b carries out the data processing that uses the input data 11 and the configuration component. The calculator 101b executes the calculating process similar to the component analyzing unit 101 shown in the first embodiment, in accordance with the face image accumulated by the input data storage device 101c and the configuration component accumulated by

the configuration component storage device 101d, and

determines the configuration component coefficient.

Then, the calculator 101b sends the determined

configuration component coefficient to the state

5   change generator 102a.

Fig. 6 is a block diagram showing an example

of the configuration of the state change generator

102a where the state change data generating unit 102

is made into an apparatus. As shown in Fig. 6, the

10   state change generator 102a includes a calculator

102c, a state-specific configuration component

storage device 102d and a state selector 102e.

The state selector 102e is specifically

realized by a semiconductor circuit for switching or

15   the like. The state selector 102e has a function for

selecting the state-specific database to extract the

configuration component to be sent to the component

analyzer 101a, in accordance with the state

information 12. The state-specific configuration

20   component storage device 102d is specifically

realized by a memory or a magnetic disc device. The

state-specific configuration component storage

device 102d has a function for accumulating the

configuration component of a face image for each state.

25   The calculator 102c is realized by a CPU that is

operated in accordance with a program. The

calculator 102c has a function for generating the

state change data in accordance with the configuration component coefficients and the configuration components of the face image for each state.

5   In this embodiment, the state selector 102e selects the state-specific database corresponding to the state information 12 and extracts the configuration component from the selected database and then sends to the component analyzer 101a. Also,

10   the state selector 102e sends the configuration component coefficients calculated by the component analyzer 101a to a component coefficient converter 103a where the component coefficient converting unit 103 is made into an apparatus. The calculator 102c

15   executes the calculation by using the equation (2), in accordance with the configuration component coefficient converted by the component coefficient converter 103a and the configuration component of the state-specific database corresponding to the

20   configuration component coefficient after the conversion, and generates the state change data.

        Fig. 7 is a block diagram showing an example of the configuration of the component coefficient converter 103a where the component coefficient

25   converting unit 103 is made into an apparatus. As shown in Fig. 7, the component coefficient converter 103a includes a calculator 103b. The calculator 103b

is specifically realized by a CPU operated in accordance with a program. The calculator 103b has a function for converting the configuration component coefficient from the state change generator 102a,

5　into the configuration component coefficient corresponding to the state-specific database different from the state-specific database corresponding to the configuration component coefficient. The calculator 103b converts the

10　configuration component coefficient by using the converting method similar to the component coefficient converting unit 103 shown in the first embodiment.

The matching data accumulator where the

15　matching data accumulating unit 104 is made into an apparatus is specifically realized by a storage device, such as a memory, a magnetic disc device and the like.

A matching device 105a where the matching unit

20　105 is made into an apparatus is different in apparatus configuration, depending on the matching method. Specifically, this is realized by a computer which has a storage device, such as a memory, a magnetic disc device and the like, and a calculator,

25　such as a CPU operated in accordance with a program and the like.

Fourth Embodiment

The fourth embodiment of the present invention will be described below with reference to the drawings. This embodiment corresponds to the apparatus where the data matching apparatus in the second embodiment is made into a specific apparatus. In this embodiment, the data matching apparatus includes: the state change generator where the state change data generating unit 102 is made into an apparatus; the matching data accumulator where the matching data accumulating unit 104 is made into an apparatus; and the matching device where the matching unit 105 is made into an apparatus.

In this embodiment, the configurations of the matching data accumulator and matching device are similar to the configurations of the matching data accumulator and matching device 105a shown in the third embodiment.

Fig. 8 is a block diagram showing an example of the configuration of a state change data generator 102f where the state change data generating unit 102 is made into an apparatus. As shown in Fig. 8, the state change data generator 102f contains a state selector 102g and calculators 102i.

The state selector 102g is specifically realized by a semiconductor circuit for switching and the like. The state selector 102g, when receiving the input data 11 and the state (ageing) information 12,

sends an input image (input data) to the calculator 102i, which carries out a neural network calculation for converting the input data 11 into a state other than the state indicated in the state information 12,

5   among the calculators 102i. The calculator 102i is specifically realized by a CPU operated in accordance with a program. Each of the calculators 102i converts the input data 11 into the face image in the state different from the state indicated in the state

10   information 12, and generates the state change data and then outputs to the matching device 105a.

In the first embodiment, the data matching method executed by the data matching apparatus may be realized by the data matching program which can

15   be executed on a calculating apparatus. Then, the data matching program may be stored in an information recording medium, which can be read in the calculating apparatus, and loaded into the calculating apparatus. Consequently, the data matching process indicated in

20   the first embodiment may be executed on the calculating apparatus.

For example, the data matching process may be executed by loading, into the calculating apparatus, the data matching program for instructing a computer

25   to execute: the process for decomposing the data of the matching target into the configuration component in the predetermined state; the process for

converting the parameter corresponding to the
configuration component in the predetermined state
into the parameter in the state different from the
predetermined state; the process for accumulating the
5   configuration component of the data classified into
each state and using the accumulated configuration
component and the converted parameter and then
generating the state change data where the
predetermined state change is given to the data of
10   the matching target; and the process for matching the
generated state change data with the matching data
group accumulated by the matching data accumulating
unit.

     Also, in the second embodiment, the data
15   matching method executed by the data matching
apparatus may be realized by the data matching program
which can be executed on the calculating apparatus.
Then, the data matching program may be stored in the
information recording medium which can be read by the
20   calculating apparatus and loaded into the calculating
apparatus so that the data matching process indicated
in the second embodiment may be executed on the
calculating apparatus.

     For example, the data matching process may be
25   executed by loading, into the calculating apparatus,
the data matching program for instructing the
computer to execute: the process for generating the

state change data where the data in the predetermined

state is changed into the data in the state different

from the predetermined state, in accordance with the

conversion using the study through the data

5   classified into each state; and the process for

matching the generated state change data with the

matching data group accumulated by the matching data

accumulating unit.